

ImagePerfect™ 2324RE

WallTex Rembrandt, Self-Adhesive (FR)

ImagePerfect™ 2324RE WallTex Rembrandt is a self-adhesive, removable, opaque and water-resistant fabric for applications such as wallpapers, wall art and wall graphics, all with outstanding print quality. It can be kiss cut or die cut, either manually or with a CAD/CAM plotter. This product has been specially created for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks, as well as UV-cured and latex inks.

ImagePerfect™ 2324RE WallTex Rembrandt is specially engineered as a self-adhesive option for printed wallpapers, wall graphics, wall stickers and wall decals on lightly structured surfaces. It offers a high print quality with remarkable text definition and a large colour gamut to ensure colourful images and vibrant area in-fills. It can be used for a wide variety of indoor and short-term outdoor applications such as point-of-sale promotions, textile billboards and posters, backgrounds in locations such as retail outlets, trade events, offices, theatres, showrooms, exhibition halls and other textile applications, such as those in lifestyle and event business locations. This material can be kiss cut and die cut on almost any plotter. A 60° tangential blade should be used. A 60° swivel blade can be substituted for simple shapes. Plotter speed should be slowed to 50%. Small shapes may be difficult to weed; the user should determine sizes appropriate to the design of the graphic. This product is PVC-free and chlorine-free.

Attention: It is important to use the matched print profile for this product as vertically applied graphics may otherwise delaminate from the substrate as a result of increased surface tension (caused by ink oversaturation). Please ensure the printed IP 2324RE is completely dry before application. It is strongly recommended for the printed media to lay flat during the drying process. IP 2324RE is not recommended for brick, non-painted cement surfaces or heavily-painted speckled walls. For application on structured surfaces, we recommend the use of the 45mm Soft Application Roller (MMSROLLEPRO), as it will press the material into the structure of the wall. Installation of the IP 2324RE should be made without the use of a heat gun because exposure to heat during application could drive shrinkage, colour fading and/or adhesive transfer to the substrate. Before the product is applied, the surface should be completely clean. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease. The wall should then be sealed/primed before application of the IP 2324RE. Recommended application tape for kiss cut and die cut graphics: ImagePerfect™ AT-500 or ImagePerfect™ AT-505.

Specifications	
Description	Self-adhesive textile
Colour	White
Thickness	180mym
Weight	N/A
Adhesive	Solvent based acrylic, removable
Adhesive Strength	8N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m²
Temperature Range	N/A
Durability (unprinted)	N/A
Flame Retardancy	B-s1, d0
Shelf Life	1 year, 20°C / 50% humidity

© September 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.