

HP Premium Vivid Color Backlit Film



The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



Achieve brilliant color and long-lasting displays

Print brilliant, long-lasting color displays fast

Produce brilliant, razor-sharp images no matter what the application. The porous coating on the printable front side of this media enhances image definition and provides excellent color contrast, even without backlight.

Maintain an efficient, productive workflow

Impress customers with quick turnaround times. Avoid smudges and smears with these fastdrying prints. Keep post-processing running smoothly with this thick, stiff film designed for easy handling to resist folds and creases, and to stay in place.

Differentiate with this recyclable film¹

Offer your customers a recyclable alternative. This film is included in the HP Large Format Media take-back program, a free and convenient return and recycling program.

Target customers	Applications	Benefits		
Print service providers	Photo enlargements	Brilliant, razor-sharp images		
	Trade show and event displays	Fast drying with Original HP pigment-based inks		
	Backlit displays	Easy to handle with a stiff, thick construction		
	POP and retail displays	In-window display permanence with a range of Original HP inks ²		
	Geographic Information Systems (GIS)	Recyclable through the HP Large Format Media take-back program ¹		

¹ HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See <u>globalbmg.com/hp/</u> <u>ecosolutions</u> for details.

With Original HP 83 UV inks or HP 91 Photo Inks or HP 771 Vivid Photo Inks. Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information,see globalBMG.com/hp/t/printpermanence.

Technical specifications



HP Premium Vivid Color Backlit Film

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit globalBMG.com/hp/.

Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see globalBMG.com/hp/MediaWarranties .						
	Q8750A	1524 mm x 30,5 m (60 in x 100 ft)	848412013498	Worldwide			
	Q8749A	1372 mm x 30,5 m (54 in x 100 ft)	848412013481	Worldwide			
	CG924A	1270 mm x 30,5 m (50 in x 100 ft)	848412014327	Asia ⁶			
	Q8748A	1067 mm x 30,5 m (42 in x 100 ft)	848412013474	North America, Europe, Asia ⁶			
	Q8747A	914 mm x 30,5 m (36 in x 100 ft)	848412013467	Worldwide			
Ordering information	Product numbers	Roll sizes	UPC Codes	Region			
Country of origin	Product of United St	Product of United States					
Recyclability	Recyclable through	Recyclable through the HP Large Format Media take-back program⁵					
Storage humidity	35 to 55% RH	35 to 55% RH					
Storage temperature	18 to 30° C / 64 to 86	18 to 30° C / 64 to 86° F					
Shelflife	2 years, unopened ir	2 years, unopened in original packaging					
Lamination	Yes, hot or cold	Yes, hot or cold					
Dry time	Less than 13 minute	Less than 13 minutes (at 23° C, 50% RH)					
Water resistance	Water resistant with	Water resistant with Original HP 771 Vivid Photo Inks ⁴					
Display permanence (Commercial in-window, laminated)	Up to 5 years with O	Up to 5 years with Original HP 83 UV inks; up to 4 years with HP 771 Vivid Photo Inks or HP 91 Photo Inks ³					
Display permanence (Commercial in-window, unlaminated)	Up to 3 years with O	Up to 3 years with Original HP 83 UV inks; up to 2 years with HP 91 Photo Inks; up to 1 year with HP 771 Vivid Photo Inks ³					
Operating humidity	20 to 80% RH	20 to 80% RH					
Operating temperature	15 to 30° C / 59 to 86	15 to 30° C / 59 to 86° F					
Finish	Matte	Matte					
Whiteness	115 per CIE Ganz 82	115 per CIE Ganz 82 Test Method, 110 per ISO 11476 Test Method					
Brightness	Greater than or equa	Greater than or equal to 86% per TAPPI T-452 Test Method					
Opacity	Greater than or equa	Greater than or equal to 77% per TAPPI T-425 Test Method, greater than or equal to 74% per ISO 2471 Test Method					
Thickness	220 microns/8.7 mil	220 microns/8.7 mil per ISO 534 Test Method					
Weight	285 g/m² per ISO 53	285 g/m ² per ISO 536 Test Method					

Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 3 Lux/12 hr day. For more information, see **globalBMG.com/hp/t/printpermanence**. Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more

information, see

5 HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. 6

Not available in Japan.



For detailed information on the HP large format printing materials portfolio and to order, see globalBMG.com/hp/

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.