

SD tuotteet

SD WB 240 Color Backlit WB



Korkealaatuinen backlit vesipohjaisille tulostimille valomainos- ja opastetuotantoon

SD WB 240 Color Backlit Film on korkealaatuinen polyesterikalvo upeiden valomainoskuvien tuotantoon. Mattapintaiselle materiaalille saadaan värikylläiset ja tarkat kuvat.

Tulostuskalvo soveltuu valokaappisovellusten lisäksi korkeatasoisten julisteiden ja ikkunamainosten toteutukseen. Tuotteessa on erinomainen hinta-laatusuhde.

- Mainonta
- Sisustaminen / tilauudistukset
- Promootiot / tapahtumat

SD WB 240 Color Backlit

SDWB2409130 / SDWB24010630

- 270g / 215mic mattapintainen polyesterikalvo
- Erinomainen tulostettavuus
- Tulostaminen: vesipohjaiset pgm ja dye-väritekniikat
- Tulostus kalvon mattapuolelle
- Ulkokesto: lyhytaikaiseen ulkokäyttöön
- Rullakoko: 1,06 x 30m
- 3" hylsy
- Jätelajittelu: sekajäte

 Vesipohjaiset pgm- ja dye-tulostimet

 Lyhytaikaiset / 1D-sovellukset

 Ulkokäyttöön

 Sisäkäyttöön

Testattava ennen varsinaista käyttöä.

Tilaa ja kokeile!

Löydät materiaalin helposti tuotekoodilla.



SERI-DECO

Seri-Deco Oy | Jussilansuora 15 04360 Tuusula

| Puh. 010 841 8080

| myynti@seri-deco.fi

| www.seri-deco.fi

BACKLIT FRONT MATTE WR 215

BACKLIT FRONT MATTE 215 is a backlit for use with dye and pigment inks. Coated substrates incorporates durability and a smooth matte, Ultra white finish print surface to provide consistent ink absorbing layer. The brilliant color expression are still stand out when the backlight was switched off. It is ideal for backlit signage applications, and provides high transmittance and ink density expressing vivid color and high resolution image. The printed side should always be faced to the observer as the inkjet coating and the print out are expected to be water-resistant.

APPLICATION

light box advertising, illuminated displays, trade show and exhibition graphics, signage

Special Backlit application

- Cosmetics
- Fashion image
- Air Port & great image application

SPECIFICATION

Caliper 215 micron (8.6 mil)
weight 270g
Base material PET
Surface Matte

Width 36", 50", 60"
Length 30m (100 ft)
Core 2"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility



Printer Compatibility

HP			EPSON			CANON
Dye	UV	Z-series	Dye	Ultra	K3	IPF
◎	★	★	◎	★	★	★

TECHNICAL DATA

Caliper 215 micron ASTM D645
Gloss 60° : 3.0 ≥ / 85° : 5.0 ≥ ASTM D2457
L.a.b 85 / 1.0 / -6.0 ANSI T
(D50/2°/Abs/No)

GUIDELINES

Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%
Use care in handling printed material, surface susceptible to abrasion
To optimize the printing quality, printer need to be set for highest print quality.

Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlamine is recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment
Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.