

# ImagePerfect™ 5700HT

## High Performance Film (FR)

**ImagePerfect™ 5700HT High Performance Film is a superior quality vinyl range with a permanent, high-tack, solvent-based adhesive. This range is available in 25 colours, including black and white which are available in both a gloss finish and also a matt finish.**

ImagePerfect™ 5700HT High Performance Film is suitable for a wide variety of indoor and long-term outdoor applications on flat and textured surfaces. The permanent, high-tack, solvent-based adhesive can be used to create a strong final bond with process security on a wide variety of surfaces including glass, stainless steel, aluminium, acrylic and also non-smooth surfaces, such as slightly textured, painted walls, MDF or hammer-tone finishes. On “hard to stick to” surfaces, we would recommend a test to confirm that the product will bond before full application takes place. Applications onto structured surfaces will require heat (until the film is soft). IP 5700HT also performs well in cold temperature environments and can be applied at temperatures as low as 5°C. In such cases, additional process security for the applied graphics can be achieved by the appropriate post heating (to warm the product). The specially-formulated, flexible, high performance films can be cut easily and weeded quickly. The high-quality, PE-coated, silicone liner promotes excellent layflat, cutting and weeding characteristics. For white vinyl, a light blue silicone liner is used to form a stronger contrast to lettering. ImagePerfect™ 5700HT High Performance Film with a gloss finish is also suitable for thermal transfer printing (with resin ribbons). ImagePerfect 5700 products are carbon measured (certified: CarbonQuota 2023)

Specifications	
Description	High performance film
Colour	Black and white (gloss and matt) and 21 colours (gloss)
Thickness	70mym
Weight	N/A
Adhesive	Solvent based acrylic, high-tack permanent
Adhesive Strength	28N/25mm (Finat TM 1/24h) <small>(Please note that the adhesive strength is qualified as per test results on black gloss. The adhesive strength on metallic colours is expected to be lower.)</small>
Release Paper	PE-coated silicone liner, 140g/m <sup>2</sup> , white vinyl with blue contrast liner
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years (black and white) 7 years (clear and colours) 5 years (metallics)
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© October 2023 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.



For more information about ImagePerfect please visit [www.imageperfect.com](http://www.imageperfect.com)

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.