HP Auto Gloss Glide GP



Soft, high-performance wrap adhesive vinyl



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Produce easy-to-install fleet graphics

Grab attention with bright, vibrant image quality

Capture vibrant graphic detail and display brilliant color and full opacity with this grey-back, adhesive vinyl. From event signage to fleet graphics, achieve a high-quality look with this versatile, easy-to-handle, permanent, conformable polymeric self-adhesive vinyl—ideal for a wide range of indoor and outdoor applications.

Easy-to-install and print, soft fleet wrap film

Soft 50-microns, high-performance adhesive vinyl for fleet and vehicle applications. Easy installation with specially formulated adhesive to glide the vinyl into place for flat and single-step recess vehicle and fleet applications. Air-release liner for quick installation. Help save time and gain efficiency with ICC profiles that help you quickly get the color you need.

Help save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time.

Target customers	Applications	Benefits
Print service providers	Full and partial vehicle wraps	High-performance, soft, polymeric calendered vinyl provides stunning print performance
	Fleet graphics	Conformable, flexible vinyl for flat and single-step recess wrap applications
	Outdoor signage and advertising	Save time with the glidable, permanent adhesive for ease of installation
	POP and retail displays	Air release, lay-flat liner enables quick installation with a smooth finish
	Event graphics	Grey adhesive provides opacity to achieve the desired hiding power
	Decals	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks



Technical specifications

HP Auto Gloss Glide GP

For the latest ICC profiles/paper presets, please visit www.printos.com.

Ink compatibility	Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks					
Thickness (base vinyl)	50 microns/2 mil per ISO 20534 Test Method					
Base vinyl	Polymeric calendered					
Liner	160 g/m² double-sided PE-coated air release liner					
Adhesive	Grey, permanent, glidable solvent-based adhesive; 2 years removable					
Opacity	>98% per TAPPI T-425 Test Method					
Finish	Gloss, >70 gloss units at 60° reflection					
Water resistance	Water resistant with HP 871 and 831 Latex Inks1					
Minimum application temperature	5 to 35°C (41 to 95°F) on clean, dry surfaces					
Service temperature	-28 to 65°C (-18 to 149°F)					
Storage temperature	21 to 24°C (69 to 75°F)					
Storage humidity	50% RH					
Lamination	Cold lamination; recommend using with HP Auto Gloss or Matte Laminate					
Shelf life	2 years, unopened in original packaging					
Unprinted durability	Up to 9 years²					
Environmental	EU and UK REACH compliant ³					
Country of origin	Product of the United Kingdom					
Ordering information	Product numb	ers Roll sizes	UPC codes	Region		
	9E0D4A	1372 mm x 45,7 m (54 in x 150 ft)	848412027662	Europe		
	9E0D5A	1600 mm x 45,7 m (63 in x 150 ft)	848412027679	Europe		
Warranty	HP large forma	HP large format printing materials are free from defects in materials and workmanship.				



¹ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: HPLEMedia.com/hp/printpermanence.

Outdoor unprinted display permanence rating based on white background color change according to SAE J2020.

³ See the HP REACH Declaration published at <u>HP Printing Products and Consumable Supplies.</u>