

AUTO Wrap 2D - Film



The AUTO brand, exclusively from Spandex, is designed to cater for the ever-changing needs of professional wrappers, detailers and fleet applicators. The products are co-branded and have been developed in conjunction with leading manufacturers. Auto offers a range of special edition automotive colours, paint protection films, digital wrap bundles, automotive tint films and accessories. The AUTO Wrap range has been manufactured by Arlon exclusively for Spandex.

PRODUCT DESCRIPTION

AUTO Wrap 2D Film is constructed of a 80 microns white gloss high performance calendered film with a tinted, clean removing, repositionable adhesive system. The repositionable light gray adhesive allows for easy installation while ensuring enough opacity for covering up existing graphics or dark substrates. The Low Profile X-Scape Technology® provides installers the benefit of a bubble-free installation combined with a smooth printed surface that doesn't show the pattern through the print. AUTO Wrap 2D works great for your multipurpose signage needs and is rated for outdoor durability up to 7 years (unprinted). Printed durability is dependent on the ink system used.

APPLICATIONS & FEATURES

- Vehicle graphics at low cost.
- One film for all-purpose applications e.g. flat tracks, cars, passenger vans, trains and trams, general signage*.
- Easy installation with X-Scape Technology®.
- Low Profile (LX) liner for a smooth, paint-like finish.
- Tinted adhesive for added opacity.
- Printable on Eco-Solvent, Solvent, Latex, and UV printers.

ADHESIVE

Clean Removing, Repositionable (Light Grey).

RELEASE LINER

Lay-Flat Polycoated with Low Profile X-Scape Technology®.

INK COMPATIBILITY:

- Solvent.
- Eco-Solvent.
- UV.
- Latex.

RECOMMENDED OVERLAMINATE:

- AUTO Wrap 2D Laminate, gloss, 35my.
- AUTO Wrap 2D Laminate, matt, 50my.

Technical Data	
Surface finish	80 to 90 Gloss Units
Gloss Meter 60° Reflection	
Thickness ⁽¹⁾	3.2-mil (80 microns)
Peel adhesion	≥ 0.70 kg/cm
Dimensional stability ⁽¹⁾	Shrinkage 0.38 mm max.
Service temperature ⁽²⁾	-29°C to 65°C
Tensile strength	2.5 kg/cm
Elongation at break	≥ 190%
Shelf life ⁽³⁾	1 year from factory shipment
Application temperature	15°C to 27°C
Available width	137.2 cm 152.4 cm
Liner release	≤ 14 g/cm
Maximum service life by specialist application	7 years
Applies for vertical outdoor exposure ⁽⁴⁾	

(1) average (2) short-term exposure (3) in original packaging, at 20° C and 50% relative humidity (4) maximum service life when applied by a specialist, and with the proper maintenance and care. Vertical outdoor weathering and central European climate. The actual and expected service life is determined by the environmental conditions, as well as pre-treatment of the substrate and regular maintenance"

PREPARATION GUIDELINE:

- The better the preparation the better the result.
- Use conventional cleaning agents and cleaning clay.
- No substances that form a coating or sealing layer by nanotechnology.
- Remove all residues of preservative wax or polishing agents.
- Finally, all surfaces must always be cleaned with Pre-Wrap Surface Cleaner.
- Thoroughly dry the vehicle – especially under rubber seals.



PRINTING CONSIDERATIONS:

- It is important to allow ink to dry as much as possible before laminating or application (min. 24h).
- Use matched component laminates.
- Work area immediately around the printer is dust and dirt free.
- The printing areas should be in clean and temperature controlled area.

USE & APPLICATION:

AUTO Wrap 2D will resist weathering best when applied to vertical or upper outboard angles. Horizontal angles, such as hood and auto roof surfaces, will deteriorate more quickly than vertical.

This is due to increased exposure to sun and moisture, as well as high deposition of dirt and atmospheric contaminants. Actual horizontal weathering will be dependent on maintenance, location and elemental exposure. AUTO Wrap 2D is designed to be used for vehicle graphics and wraps with flat or simple curves. When wrapping curves and channels it is recommended the product be draped and not stretched into areas with channels. Can be applied on low profile rivets. Please note that rivets vary in shape and size so tenting may appear

APPLICATION GUIDELINE:

- Clean and dust free room, preferably with car lift or mounting ramp.
- Make sure you thoroughly clean all areas.
- Minimum temperature +15 °C rapid evaporation of residual moisture.
- When using air-egress adhesive vinyl, applications require even more squeegee pressure to ensure the adhesive makes a firm bond.
- Adhesion builds up smoothly.
- After application, the adhesive must be allowed to harden before going into service. The absolute minimum time would be 24 hours.

MAINTENANCE GUIDELINE:

- 3 days after application: cleaning in car wash is possible.
- No high pressure cleaning recommended.
- For Long-Lasting film properties we recommend to regularly use cleaning and care products.

POST-CARE & CLEANING INSTRUCTIONS:

Fleet graphics films can be easily cleaned using a pressure washer but can be damaged just as easily by improperly handling the water spray or incorrectly blending the cleaning solutions. Regular washing is highly recommended to avoid the necessity of deep cleaning and to prevent accumulating dirt. In order to keep the vinyl from degrading or lifting around the edges while pressure washing, it is important to adhere to the following guidelines:

1. Nozzle pressure should never exceed 1,300 PSI.
2. Water temperature should never exceed 140°F (60°C).
3. Nozzle tip should never be closer than five feet from the graphics.
4. Angle of water spray should be no shallower than 60° from perpendicular. Keep the nozzle spray pattern perpendicular to the overlapping direction.
5. Detergent solutions should always be blended with water at the correct ratio and pH (between 6 and 8). A more concentrated solution can damage both the adhesive and vinyl.
6. A post-washing, fresh-water rinse will help maintain the life of the paint and vinyl.

REMOVABILITY GUIDELINE:

1. Heat the area to be removed evenly with your heat source to approximately 125°F (50°C). In some climates the sun will give sufficient heat to do this. If temperatures exceed 125°F (50°C) the vinyl may delaminate leaving the adhesive behind making the removal much more difficult.
2. Gently lift the edge of the graphic. When you have removed enough to get a good hand hold, begin lifting the graphic by pulling away from the vehicle at a 15° angle. Do not pull the vinyl away from the vehicle at an angle greater than 90° as this will cause the vinyl to delaminate leaving the adhesive behind.
3. Try to keep the leading edge of the removal in a straight line by spreading your fingers out along the top of the removed graphic. Pull slowly for a clean removal.

APPLICATION TRAINING:

Training & education is the key to success a perfect installation. Spandex offers regular training for customers interested in application courses. Please contact your local Spandex for more information.

NOTE: Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. We also recommend to test compatibility on raw & primed MDO prior to installation due to variation in substrate properties. Furthermore, the application information published by AUTO must be considered.

IMPORTANT NOTICE: All AUTO products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning AUTO products is based upon research which the company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of AUTO products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

DISCLAIMER GENERAL: Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading. Spandex gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Spandex's general terms and conditions of sale. Spandex's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Spandex be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.