

ImagePerfect™ 2333 Grey Back Fabric is a soft polyester that is equipped with a grey back side for a wide variety of blockout textile applications. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent, solvent, UV-cured and latex inks.

IP 2333

ImagePerfect™ 2333 is a polyester fabric that is ideal for a wide variety of soft signage, textile, display applications with 100% opacity, including roll-up displays, backdrops, textile billboards and advertising banners, with the opacity being achieved via the inclusion of a grey coating on the back side of the product. It will be used in many different locations, including offices, retail environments, lifestyle business locations (bars, hotels, restaurants, cinemas, sports arenas, casinos, etc) and event business locations (trade shows, show rooms, conference facilities, etc). It can be used for indoor installations only. It offers a high-quality print finish with remarkable text definition and a large colour gamut to ensure colourful images and vibrant area in-fills. It delivers outstanding layflat properties with no curling, together with no fraying of the edges. This product is PVC-free and chlorine-free and it meets the requirements of ISO 14001.

Specifications	
DESCRIPTION	Polyester banner
COLOUR	White matt
THICKNESS	300μ
WEIGHT	300g/m ²
TENSILE STRENGTH	N/A
TEAR RESISTENCE	N/A
TEMPERATURE RANGE	N/A
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	B-s1, d0
SHELF LIFE	1 year, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© December 2020 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information. They are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use, not least with regard to possible application-related influences. All technical data are subject to change.

The durability expectation is based on mid European exposure conditions. The actual performance life will depend on substrate preparation, exposure conditions and the maintenance of the applied product. For instance, exterior performance will typically decrease in the case of installations facing south, in areas of extended exposure to high temperatures (such as southern European countries), in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will typically be impacted.

In the event of improper use and/or incorrect processing that does not comply with our instructions, any liability is excluded, including that for follow-up costs.

Digital: The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents could otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ print media.