Maximize productivity and deliver high-value jobs with consistent quality



*Product image may differ from actual product

CONSISTENT QUALITY-Produce highvalue applications

- Deliver stunning prints with uniform colors via precise HP Pixel Control ink mixing and distribution.
- Achieve consistent quality across jobs and create color profiles with the HP Embedded Spectrophotometer.
- With HP Latex inks, print a wide range of signage and décor jobs, now with automated double-sided printing¹
- Expand into profitable new applications with the easiest white ink experience². 30% faster³ in underflood, 3 layers and 5 layers.

SIMPLIFIED PRODUCTION-Optimize printing processes

- Reduce inventory management with universal printheads and the new 50% extended life maintenance cartridge⁴.
- Load media quickly and easily with spindle-less front-loading and save media by printing from the leading edge 5 .
- Reach production speeds up to 334 ft² (31 m²)/hour⁶ and avoid waiting times with prints that dry instantly.
- Streamline your print workflow with our intuitive end-to-end software solution: HP PrintOS Production Hub.

LEAD THE WAY-Win with sustainable solutions

- Create a comfortable workspace⁸ with odorless prints⁹ and UL ECOLOGO®certified¹⁰ HP Latex Inks.
- Advance your sustainability journey with our unique HP PrintOS Sustainability Amplifier¹¹ software.
- Reduce plastic waste with returnable supplies via HP Planet Partners including new maintenance cartridge.
- Stand out in the market with the only EPEAT Climate+13 registered printers in the signage industry.

Messaging Footnotes

¹ Automated double-sided printing compatible with PVC-free media.

² Automatic White Ink Recirculation System between the HP Latex 832 Ink Mix and HP 832 White Latex Ink Cartridge. When not printing with white ink remove the white printheads from the carriage and store them in the offline rotation chamber, avoiding unnecessary white ink waste. White print modes (spot, underflood, overflood, 3 layers, and 5 layers) are available with white ink densities up to 260%.

3 Faster white ink printing in underflood, 3 layers and 5 layers white modes compared to HP Latex 700 and 800 Printer series thanks to new drying system with extra drying capacity. Test conducted in January 2025.

At least 50% more life thanks to a 40% longer cleaning cloth and new ink collection unit that uses 100% of the cleaning cloth compared to previous maintenance cartridge model.

Finding from the leading edge is compatible with the following media categories: self-adhesive vinyl, canvas, and heat transfers. Compatibility with PET films, papers, and polypropylenes depends on media

characteristics.

6 Draft mode (4-pass, 4 color, 90% ink density). Based on internal HP testing in January 2025 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

7 For HP's large-format printers, HP PrintOS Production Hub is compatible with HP Latex printers and the HP Stitch Printer series. HP PrintOS Production Hub premium features are only accessible when purchasing an HP Professional Print Service Plus Plan.

8 Based on odor sensory evaluation when printing with the HP Latex 630 series printer and Mimaki UJV 100-160. Tests done in a 57 m² room with 5ACH. Test conducted by Odournet following the standard VDi3882, where

the HP Latex 630 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UJV 100-160. HP Latex 730/830 printers are using the same inks and are in the same category as

he HP Latex 630.

9 Applicable to HP Latex Inks. Based on sensory evaluations conducted by Odournet, done according to VDI Guideline 3882 where 832 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

10 UL ECOLOGO® Certified HP 832 inks meet a range of stringent human health and environmental considerations. For certifications, see www.ul.com/EL and www.ul.com/gg

11 The HP Sustainability Amplifier program helps customers reduce their environmental impact through self-assessment, resources, and recognition with an HP badge, not an official eco-label. Recognition is subject to approval for credibility. Program is only available in English.

12 Program availability varies. For details, see hp.com/hprecycle

13 The HP Latex 730 and 830 series is EPEAT Gold in the U.S. and Canada and has achieved EPEAT Climate+. See www.epeat.net for registration status and tier levels by country. As of January 2025, no other competitors in the signage market have been registered in EPEAT.




















Technical specifications

Print	
Print speed	31 m²/hr - Draft (4-pass) in Banner¹; 21 m²/hr - Speed (6-pass)²; 17 m²/hr - Standard (8-pass)²; 16 m²/hr - Quality (12-pass)²; 11 m²/hr - High Quality (16-pass)²; 17 m²/hr - White Spot 60w²; 9 m²/hr - White Overflood 60w²; 4.4 m²/hr - White Underflood 100w²; 3 m²/hr - White 3 layers 160w²; 1.5 m²/hr - White 5 layers²;
Print resolution	Up to 1200 x 1200 dpi
Technology	HP Latex Printing Technologies
Ink types	Water-based HP Latex Inks
ink cartridges	10 (Cyan, Magenta, Yellow, Black, Light Cyan, Light Magenta, White, Optimizer, Overcoat) cartridges
Cartridge size	1L per cartridge
Printheads	10 (7 HP Latex Printhead, 1 HP Latex Optimizer, 2 HP Latex White Printhead)
Media	
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers
Handling	Roll feed, take-up reel, wiper roller ³ , media saver, automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper-based media, and film)
Media rolls	1
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support);
Maximum roll weight	55 kg;
Maximum roll diameter	250 mm;
Maximum media width	1625 mm;
Thickness	Up to 0.5 mm;
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles 5
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (WxDxH	
Product	2583 x 852 x 1402 mm;

purge syringe kit, power cords, user maintenance kit, edge holders, 2-in spindle adaptor, lubrication felts kit, edge holders, 2-in spindle adaptor, lubrication felts kit, edge reference guide, documentation software, spanner size 17, screwdriver t-2 guide, spanner size 17, screwdriver t-2 guide, documentation software, spanner size 17, screwdriver t-2 guide, spanner size	Shipping	2800 x 1130 x 1270 mm;
Product 261 kg; Shipping 368 kg; Included What's in the box HP Latex 730 W Printer, White ink module, printheads, maintenance cartridge with ink collection unit, additional ink collection unit, printer stand, take-up reel, Condensation collector kit, empty cartridge for white ink recirculation, manua purge syringe kit, power cords, user maintenance kit, edge holders, 2-in spindle adaptor, lubrication felts kit, quick reference guide, documentation software, spanner size 17, screwdriver to guide, documentation software, spanne	Operating area	2793 x 2100 mm;
Shipping 368 kg: Included What's in the box HP Latex 730 W Printer, White ink module, printheads, maintenance cartridge with ink collection unit, additional ink collector kit, empty cartridge for white ink recirculation, manual purge syringe kit, power cords, user maintenance kit, edge holders, 2-in spindle adaptor, lubrication felts kit, quick reference guide, documentation software, spanner size 17, screwdriver to perating temperature Environmental ranges Operating temperature 15 to 30°C; Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 w (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cord Carda((CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICSA), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udeets AgBB criteria, French V	Weight	
Included What's in the box HP Latex 730 W Printer, White ink module, printheads, maintenance cartridge with ink collection unit, additional ink collection unit, printer stand, take-up reel, Condensation collector kit, empty cartridge for white ink recirculation, manual purge syringe kit, power cords, user maintenance kit, edge holders, 2-in spindle adaptor, lubrication felts kit, quick reference guide, documentation software, spanner size 17, screwdriver t-2. Environmental ranges Operating temperature 15 to 30°C; Operating temperature 15 to 30°C; Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 w (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICSS), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Udraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB c	Product	261 kg;
What's in the box HP Latex 730 W Printer, White ink module, printheads, maintenance cartridge with ink collection unit, additional ink collection unit, printer stand, take-up reel, Condensation collector kit, empty cartridge for white ink recirculation, manua purge syringe kit, power cords, user maintenance kit, edge holders, 2-in spindle adaptor, lubrication felts kit, quick reference guide, documentation software, spanner size 17, screwdriver £2 Environmental ranges Operating temperature 15 to 30°C; Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant; Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Shipping	368 kg;
maintenance cartridge with ink collection unit, additional ink collection unit, printer stand, take-up reel, Condensation collector kit, empty cartridge for white ink recirculation, manua purge syringe kit, power cords, user maintenance kit, edge holders, 2-in spindle adaptor, lubrication felts kit, quick reference guide, documentation software, spanner size 17, screwdriver to the spanne	Included	
Operating temperature 15 to 30°C; Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	What's in the box	maintenance cartridge with ink collection unit, additional ink collection unit, printer stand, take-up reel, Condensation collector kit, empty cartridge for white ink recirculation, manual
Acoustics Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power	Environmental ranges	
Acoustics Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (33 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950.1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Operating temperature	15 to 30°C;
Sound pressure Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep) Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Operating humidity	20 to 80% RH (non-condensing)
Sound power Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep)	Acoustics	
Power Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Sound pressure	Printing: 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Consumption 1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.2 W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Sound power	Printing: 7.8 B(A) (operating), 5.5 B(A) (idle), <4.0 B(A) (sleep)
W (off) Requirements Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Power	
Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord Certification Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Electromagnetic Compliant with Class A requirements, including; USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR*, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Consumption	1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <19 W (sleep), <0.25 W (off)
Safety IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Requirements	
Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC Electromagnetic Compliant with Class A requirements, including: USA (FCC rule Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Certification	
Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)
Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, U	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)
	Environmental	Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, UL
Warranty One-year limited hardware warranty	Warranty	One-year limited hardware warranty

Ordering information

Product

070004	LID Later 700 W Delater	
870B8A	HP Latex 730 W Printer	
Accessories		
21V10A	HP Latex 600/700/800 Series User Maintenance Kit	
421S3A	HP Latex Substrate Saver Accessory	
7HR18A	HP Latex 700/800 Series Ink Collector Foams Kit	
7HR19A	HP Latex Substrate Loading Accessory	
A14CFA	HP Latex 730/830 Wiper Roller Installation Kit	
A4AN0A	HP Latex 730/830 Textile Kit Accessory	
A4AN1A	HP Latex Edge Holders Accessory	
T7U73A	HP Latex 500/700/800 Wiper Roller	
Original HP printing supplies		
4UU93A	HP 836 White Latex Printhead	
4UU94A	HP 836 Optimizer Latex Printhead	
4UU95A	HP 836 Universal Latex Printhead	
4UV29A	HP 832 1-liter White Latex Ink Cartridge	
4UV75A	HP 832 1-liter Black Latex Ink Cartridge	
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge	
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge	
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge	
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge	
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge	
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge	
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge	
4UV83A	HP 832 Ink Mix Container	
9T063A	HP 838 Latex Maintenance Cartridge	
9T064A	HP 833/838 Latex Ink Collection Unit (2-unit pack)	

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks Original HP large format printing materials

HP PVC-free Wall Paper (REACH compliant⁶, UL **GREENGUARD** Gold Certified⁷, FSC[®] certified⁸, meets AgBB criteria⁹, CE¹⁰, UKCA¹¹, PVC-free¹²,)
HP Permanent Gloss Adhesive Vinyl (REACH compliant⁶)
HP Recycled¹³ Removable Adhesive Fabric, 3-in Core (Latex/solvent)

For the entire HP Large Format Printing Materials portfolio, please see

Service and Support

UG9C1E HP 2 year PLUS Service Plan for HP Latex 730 White (In Warranty)
UG9C2E HP 3 year PLUS Service Plan for HP Latex 730 White (In Warranty)
UG9C3E HP 4 year PLUS Service Plan for HP Latex 730 White (In Warranty)
UG9C4E HP 5 year PLUS Service Plan for HP Latex 730 White (In Warranty)
UG9C5PE HP 1 year Post Warranty PLUS Service Plan for HP Latex 730 White UG9C6PE HP 2 year Post Warranty PLUS Service Plan for HP Latex 730 White

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

Specification Footnotes

Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.

Printmode names in color modes are based on Self-Adhesive Vinyl applications. Names and Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects and the application you produce.

³ Wiper roller is an optional accessory.
⁴ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test

⁵ Textile Kit Accessory required for long runs of textile and porous textile.
⁶ See the HP REACH Declaration published at https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c05996997

"See the HP REACH Declaration published at https://nculvis.www2.np.com/v2/Jett.Document.aspx/acordame=cus999997
"OLL GREENGUARD Gold Certified into: +IP PVC-free Wall Paper printed with Original HP Latex like is UL GREENGUARD Gold Certified; UL GREENGUARD Gold Certified into: +IP VC-free Wall Paper printed with Original HP Latex like is UL GREENGUARD Gold Certified; UL GREENGUARD Gold Certified into: +IP VC-free Wall Paper printed with Original HP Latex like is UL GREENGUARD Gold Certified; UL GREENGUARD Gold Certified or to: +IP VC-free Wall Paper printed with HP Latex likes are certified papers that are sourced from FSC*-certified forests and other controlled sources. BMG trademark license code FSC*-C115319, see fsc.org. HP trademark license code FSC*-C115743, see fsc.org, Not all FSC*-certified products are available in all regions.

9 AgBB - HP PVC-free Wall Paper printed with HP Latex likes meets AgBB criteria for health-related evaluation of VOC emissions of indoor building products. See umweltbundesamt.de/en/topics/health/commissions-working-

groups/committeefor-health-related-evaluation-of-building.

10 CE mark - Self-declared according to European Standard EN15102.

10 UKCA compliant - Self-declared according to European Standard EN15102 and UKCA.

12 PVC-free alternative - Based on HP internal and third-party testing chemical analysis that demonstrates elemental chlorine to be at or below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the paper.

making process, and not due to the presence of PVC.

13 Product consists of PET fabric and coatings. With liner attached, 69% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.

© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. May 2025 eu-en

